

SOLID TO SUCCEED.



XC 958U

XC958U

.....
► **Highlight:**

XCMG advanced variable hydraulic system continuously and automatically matches the hydraulic flow with the machine performance desired base on need, ensures the working device and steering fuctions high efficiency and lowe fuel consumption. AC is equipped with eleven all-around outlets to keep the cabin at a comfortable temperature. Dual filter replaced protect cab from dust entering.

XCMG North America Corportation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



DIMENSIONS & SPECIFICATIONS		GENERAL PURPOSE QUICK CHANGE				HIGH LIFT QUICK CHANGE			
	Bucket capacity	3.1m ³	4.0 yd ³	3.5m ³	4.6 yd ³	3.1m ³	4.0 yd ³	3.5m ³	4.6 yd ³
A	Height to Top of Exhaust Pipe	3,285 mm	10.78 ft ³	3,285 mm	10.78 ft	3,285 mm	10.78 ft	3,285 mm	10.78 ft
B	Height to Top of Cabin	3,475 mm	11.40 ft ³	3,475 mm	11.40 ft	3,475 mm	11.40 ft	3,475 mm	11.40 ft
C	Height to Top of Warning Beacon	3,830 mm	12.57 ft	3,830 mm	12.57 ft	3,830 mm	12.57 ft	3,830 mm	12.57 ft
D	Ground clearance	425 mm	1.39 ft	425 mm	1.39 ft	425 mm	1.39 ft	425 mm	1.39 ft
E	Wheelbase	3,550 mm	10.99 ft	3,550 mm	10.99 ft	3,350 mm	10.99 ft	3,350 mm	10.99 ft
F	Overall Length (without bucket)	7,065 mm	23.18 ft	7,065 mm	23.18 ft	7,280 mm	23.88 ft	7,280 mm	23.88 ft
G	Shipping length (with bucket level on ground)	8,720 mm	28.61 ft	8,620 mm	28.28 ft	8,810 mm	28.90 ft	8,710 mm	28.58 ft
H	Hinge Pin Height at Carry Position	460 mm	1.51 ft	460 mm	1.51 ft	525 mm	1.72 ft	525 mm	1.72 ft
I	Hinge Pin Height at Maximum Lift	4,155 mm	13.63 ft	4,155 mm	13.63 ft	4,450 mm	14.60 ft	4,450 mm	14.60 ft
J	Lift Arm Clearance at Maximum lift	3,560 mm	11.68 ft	3,560 mm	11.68 ft	3,755 mm	12.32 ft	3,755 mm	12.32 ft
K	Dump Clearance at Maximum lift and 45° Discharge	2,980 mm	9.78 ft	2,915 mm	9.78 ft	3,510 mm	10.74 ft	3,210 mm	10.53 ft
L	Reach at Maximum Lift and 45° Discharge	1,340 mm	4.40 ft	1,400 mm	4.59 ft	1,280 mm	4.20 ft	1,340 mm	4.40 ft
M	Dump Angle at Maximum Lift and Dump (on stops)	45°	45°	45°	45°	45°	45°	45°	45°
N	Roll back Angle	Ground	42°	42°	42°	42°	42°	42°	42°
		Carry	46°	46°	46°	47°	47°	47°	47°
O	Turning Radius Outside of Tires	5,995 mm	19.67 ft	5,995 mm	19.67 ft	5,995 mm	19.67 ft	5,995 mm	19.67 ft
P	Turning Radius Inside of Tires	3,215 mm	10.55 ft	3,215 mm	10.55 ft	3,215 mm	10.55 ft	3,215 mm	10.55 ft
Q	Width over Tires (unloaded)	2,780 mm	9.12 ft	2,780 mm	9.12 ft	2,780 mm	9.12 ft	2,780 mm	9.12 ft
R	Tread Width	2,180 mm	7.15 ft	2,180 mm	7.15 ft	2,180 mm	7.15 ft	2,180 mm	7.15 ft
S	Dig Depth	90 mm	0.30 ft	90 mm	0.30 ft	80 mm	0.26 ft	80 mm	0.26 ft
T	Overall Height	5,620 mm	18.44 ft	5,710 mm	18.73 ft	5,915 mm	19.41 ft	6,010 mm	19.72 ft
U	Turning Radius Over bucket	6,875 mm	22.56 ft	6,855 mm	22.49 ft	6,940 mm	22.77 ft	6,920 mm	22.70 ft
V	Gradeability	29°	29°	29°	29°	29°	29°	29°	29°
W	Bucket Width	2,996 mm	9.83 ft	2,996 mm	9.83 ft	2,996 mm	9.83 ft	2,996 mm	9.83 ft
X	Articulation Angle	40°	40°	40°	40°	40°	40°	40°	40°
Tipping load	Static tipping load: straight	12,200 kg	26,896 lb	12,200 kg	26,896 lb	11,320 kg	24,956 lb	11,320 kg	24,956 lb
	40° full turn	10,600 kg	23,369 lb	10,600 kg	23,369 lb	10,000 kg	22,046 lb	10,000 kg	22,046 lb
	Breakout force	175 kN	39,342 lbf	165 kN	30,094 lbf	165 kN	30,094 lbf	175 kN	39,342 lbf
	Operating weight	19,600 kg	43,211 lb	19,730 kg	43,497 lb	19,650 kg	43,321 lb	19,780 kg	43,607 lb

