

SOLID TO SUCCEED.



XCT



XCT35U

- ▶ Matching mainstream brand chassis Freightliner and Kenworth, it adds swing proportional braking, winch amplitude wireless remote control, swing maximum speed adjustment, etc.
- ▶ High lifting performance, extreme arm length design, 4-section main arm arm length 120ft;
- ▶ The new energy-saving hydraulic system has better micro-movement and leading control performance;
- ▶ Brand new appearance and humanized design.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

MAIN PERFORMANCE

ITEM		UNIT	PARAMETER
Max. total rated lifting capacity		USt	35
Min. rated range		ft	6
Turning radius at turntable tail		ft	6.43
Max.load moment	Base boom	lb ^f *ft	484,000
	Fully-extended boom	lb ^f *ft	285,100
	Fully-extended boom + Jib	lb ^f *ft	181,000
Outrigger span (fully-extended)	Longitudinal	ft	18.2
	Lateral	ft	20
	Base boom	ft	37
	Fully-extended boom	ft	120
	Fully-extended boom + Jib	ft	143
	Base boom	ft	36.4
	Fully-extended boom	ft	120
	Fully-extended boom + Jib	ft	149.8
Jib offset angle		°	0, 15, 30

WORKING SPEED

ITEM		UNIT	PARAMETER
Lifting boom elevating time		s	35
Fully-extended time of lifting boom		s	50
Max. slewing speed		rpm	2
Horizontal outrigger	Extending Simultaneously	s	≤ 25
	Retracting Simultaneously	s	≤ 22
Vertical outrigger	Extending Simultaneously	s	≤ 35
	Retracting Simultaneously	s	≤ 30
Speed (single line, 4th layer)	Main winch system	fpm	426

