

Standard Bucket Capacity:
0.42 - 0.78 yd³ (0.32 - 0.6 m³)

SOLID TO SUCCEED.



Operating Weight:
33,069 lb (15,000 kg)

Rated Power:
121 hp (90 kW)



HYDRAULIC EXCAVATORS

XE155U

- ▶ The newly engineered XE135U builds on the concept of robust power and longer durability of mid size excavators of XCMG. All systems have been designed on the basis of harmonious matching of sufficient power, hydraulic flow, versatility, low fuel consumption and equipped with exhaust treatment system to meet the EPA regulations.
- ▶ If you are looking for a tough machine from a durable brand you can trust to get your work done with efficiency, look no further than our XE135U. Its versatile design and innovative features deliver the performance you expect to do various difficult jobs.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

TECHNICAL SPECIFICATIONS

ITEM	CONTENT	XE155U
Engine	Model	Cummins F3.8
	No. of cylinders	4
	Rated power at 2100 rpm (SAE J1995)	121 hp (90 kW) at 2,200 rpm
	Max. torque at 1500 rpm	369 lb.ft (500 N · m)
	Idle (low-high)	950 - 1,100 rpm
	Piston displacement	232 in³ (3.8 L)
Pump flow & System pressure	Main pumps, type:	2 x variable displacement tandem axial piston pumps
	Maximum flow at 1800 rpm	2x31.7+11.7 gal/min (2x120+53 L/min)
	Pilot pumps, type:	Gear pump
	Maximum flow at 1800 rpm	4.8 gal/min (18 L/min)
Speed & Traction	Travel speed (low - high)	1.8 - 2.9 mph (2.9 - 4.7 km/h)
	Maximum traction force	27,202 lbf (121 kN)
	Maximum gradeability	70% / 35°
Digging Forces	Bucket (Normal/Press. Up) - kN/lbf	66 gal (250 L)
	Arm (Normal/Press. Up) - kN/lbf	6.6 gal (25 L)
Fluid Capacity	Fuel tank	25.1 gal (95 L)
	Urea (def) tank	2.9 gal (11 L)
	Hydraulic oil tank	24,055/107
	Engine oil	17,985/80
Working Range	Maximum digging reach	27'3"/8,295
	Maximum digging depth	18'2"/5,535
	Maximum loading height	20'3"/6,160
	Minimum loading height	6'10"/2,095
	Maximum digging height	28'4"/8,630
	Maximum vertical wall depth	15"/4,580
	Minimum swing radius	8'1"/2,475
Dimensions	Tail swing radius	7'9"/2,370
	Shipping height (boom)	9'7"/2,930
	Shipping height (Cab)	9'11"/3,035
	Shipping length	25'6"/7,780
	Shipping width	8'6"/2,590
	Counterweight clearance	37"/931
	Height over cab	9'5"/2,870
	House width	8'2"/2,490
	Cab height above house	30"/766
	Cab width	3'7"/1,096
	Tumbler distance	9'7"/2,910
	Track length	11'11"/3,630
	Undercarriage width	8'6"/2,590
	Shoe width std.	24"/600
	Track height	32"/803
	Ground clearance	19"/476

