

SOLID TO SUCCEED.



Standard Bucket Capacity:
2.1 yd³ (1.6 m³)

Operating Weight:
76,059 lb (34,500 kg)

Rated Power:
232 hp (173 kW)

XE



HYDRAULIC EXCAVATORS

XE300U

- ▶ The newly upgraded XE300U builds on its reputation as one of the most sold and appreciated excavators of XCMG. All systems have been designed based on evaluation of customer demands including sufficient power, hydraulic flow, versatility, low fuel consumption and environmental protection features.
- ▶ If you are looking for a tough machine from a durable brand you can trust to get your work done with efficiency, look no further than our XE300U. Its versatile design and innovative features delivery the performance you expect to do various difficult jobs.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

TECHNICAL SPECIFICATIONS

ITEM	CONTENT	XE300U
Engine	Model	Cummins B6.7
	No. of cylinders	6
	Rated power at 2,000 rpm (SAE J1995)	232 hp (173 kW) at 2,000 rpm
	Max. torque at 1,500 rpm	700 ft • lbf (949 N • m)
	Piston displacement	1.8 gal (6.7 L)
Pump flow & System pressure	Main pumps, type:	2 x Variable displacement tandem axial piston pumps
	Maximum flow at 2,000 rpm	2x84.5 gal/min (2x320 L/min)
	Pilot pump, type:	Gear pump
	Maximum flow at 2,000 rpm	6 gal/min (23 L/min)
Speed & Traction	Travel speed (low - high)	2.1 - 3.4 mph (3.3 - 5.5 km/h)
	Maximum traction	57,461 lbf (255.6kN)
	Maximum gradeability	70% / 35°
Digging Forces (ISO 6015)	Bucket - kN/lbf	47,435 lbf (211 kN)
	Arm - kN/lbf	36,869 lbf (164 kN)
Fluid Capacity	Fuel tank	137 gal (520 L)
	Urea (DEF) tank	12.7 gal (48 L)
	Hydraulic oil tank	58 gal (220 L)
	Engine oil	6.3 gal (24 L)
Working Range	Maximum digging reach	35'6"/10,830
	Maximum digging depth	23'7"/7,021
	Maximum loading height	23'9"/7,232
	Loading height	8'3"/2,520
	Maximum digging height	34'10",360
	Minimum swing radius	13'3",962
Dimensions	Tail swing radius	10'5"/3,174
	Shipping height (boom)	11'8"/3,552
	Shipping height (guardrail)	11'3",337
	Shipping length	34'4"/10,470
	Shipping width	11'1"/3,390
	Counterweight clearance	4'1",223
	Height over cab	10'6"/3,207
	Upper structure width	2,970
	Track length on ground	13'2"/4,024
	Track length	16'2"/4,930
	Undercarriage width	11'1"/3,390
	Shoe width std.	31"/800
	Track height	3'6"/1,059
	Ground clearance	21"/538
	Track gauge	8'6"/2,590

