

Standard Bucket Capacity:
0.16 yd³ (0.12 m³)

SOLID TO SUCCEED.



Operating Weight:
9,259 lb (4,200 kg)
with canopy:
9,039 lb (4,100 kg)

Rated Power:
24.4hp (18.2 kW)



MINI EXCAVATORS

XE35U

The XE35U comes with every feature you expect from a mini excavator in its tonnage.

- ▶ Variable angle boom, 75° to the left and 50° to the right, and zero swing tail give you an edge when undertaking operations wherever space is confined.
- ▶ Powered by a reliable 24.4hp YANMAR engine, you can count on it to finish tough jobs in various operating conditions. When it comes to efficiency, versatility is a critical factor. That's why the machine is compatible to multiple attachments that can be installed within a short period of time with its hydraulic quick coupler. You will make full use of every second in the jobsite.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

ITEM	CONTENT	XE35U
Engine	Make/model	YANMAR/3TNV88F/Tier 4F
	Fuel/cooling	Diesel/Liquid, forced circulation
	No. of cylinders	3
	Piston displacement	0.4 gal (1.6 L)
	Power output (ISO 14,396)	24.4 hp (18.2 kW) / 2,200 rpm
	Max torque	62.9 - 69.5 ft.lb (85.3 - 94.2 N·m) 1,320 rpm
Pump	Total hydraulic capacity	26.15 gal/min (99 L/min)
	AUX1 & AUX 2 Maximum flow rate	13.2 gal/min (50 L/min)
	AUX1/AUX 2 standard relief pressure	2,610/3,626 psi (180/250 bar)
Speed & Traction	Travel speed (low - high)	1.4 - 2.2 mph (2.2 - 3.6 km/h)
	Traction force	7,104 lbf (31.6 kN)
	Gradeability	30°
Digging Forces	Digging force, standard arm (ISO 6,015)	4,564 lbf (20.3 kN)
	Digging force, long arm (ISO 6,015)	6,430 lbf (28.6 kN)
Fluid Capacity	Fuel tank	10.57 gal (40 L)
	Hydraulic tank	9.25 gal (35 L)
Working Range	Maximum digging height	16'5" (5,000 mm)
	Maximum digging depth	10' (3,060 mm)
	Maximum dumping height	11'10" (3,600 mm)
	Maximum vertical wall digging depth	7'5" (2,260 mm)
	Minimum swing radius	7'1" (2,170 mm)
	Maximum digging reach at ground level	17'1" (5,200 mm)
	Maximum digging reach	17'5" (5,300 mm)
	Maximum dozer lifting height	12" (305 mm)
	Maximum dozer cutting depth	14" (360 mm)
Dimensions	Overall length	16'3" (4,960 mm)
	Tail slew radius	34" (870 mm)
	Tumbler length	15'8" (721 mm)
	Track length	7'3" (2,200 mm)
	Dozer blade, maximum reach at ground level	5'3" (1,590 mm)
	Undercarriage length	8'10" (2,690 mm)
	Dozer blade height	14" (367 mm)
	Overall width	5'9" (1,740 mm)
	Track gauge	4'9" (1,440 mm)
	Minimum ground clearance	12" (297 mm)
	Track height	21" (531 mm)
	Ground clearance of counterweight	23" (587 mm)
	Overall height of tank hood	5'3" (1,590 mm)
	Overall height	8'4" (2,535 mm)
	Track shoe width	12" (300 mm)
	Working width at maximum right-hand rotation	6'7"(2,005 mm)
	Working width at maximum left-hand rotation	15'8" (728 mm)
	Maximum boom offset to the right	30" (770 mm)
	Maximum boom offset to the left	23" (580 mm)
	Maximum boom swing angle to the right	75°
	Maximum boom swing angle to the left	50°

