

Standard Bucket Capacity:
0.21 yd³ (0.16 m³)

SOLID TO SUCCEED.



Operating Weight:
12,566 lb (5,700 kg)

with canopy:
12,346 lb (5,600 kg)

Rated Power:
41.2hp (30.7 kW)



MINI EXCAVATORS

XE55U

The XE55U comes with every feature you expect from a compact excavator in its tonnage.

- ▶ Variable angle boom, 70° to the left and 53° to the right, reduced swing tail, and standard rubber track and angle blade gives you an edge when undertaking operations in confined sites such as utility, garden, and community landscapes.
- ▶ Powered by a reliable 41.2hp Kubota engine, you can count on it to finish tough jobs in various operating conditions. When it comes to efficiency, versatility is a critical factor. That's why the machine is compatible to multiple attachments that can be installed within a short period of time with its hydraulic quick coupler. You will finish the operations with ease and comfort in the jobsite.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

ITEM	CONTENT	XE55U
Engine	Make/model	Kubota/V2403/Tier 4F
	Fuel/cooling	Diesel/Liquid, forced circulation
	No. of cylinders	4
	Piston displacement	0.6 gal (2,434 cm ³)
	Power output (ISO 14396)	41.2 hp (30.7 kW)
	Max torque	117.9 ft.lb/1500 rpm (159.8 N·m/1500 rpm)
Pump	Total hydraulic capacity	148.1 gal/min (58.4 L/min)
	AUX 1 Maximum flow rate	29 gal./min (110 L/min)
	AUX 2 Maximum flow rate	19.8 gal./min (75 L/min)
	AUX 1 standard relief pressure	3,045 psi (210 bar)
	AUX 2 standard relief pressure	2,465 psi (170 bar)
Speed & Traction	Travel speed (low - high)	1.7 - 2.9 mph (2.8 - 4.6 km/h)
	Traction force	11,869.9 lbf. (52.8 kN)
	Gradeability	70%/35°
Digging Forces	Digging force, standard arm (ISO 6015)	5,462.9 lbf. (24.3 kN)
	Digging force, long arm (ISO 6015)	5,260.5 lbf. (23.4 kN)
	Digging force, bucket (ISO 6015)	10,004 lbf. (44.5 kN)
Fluid Capacity	Fuel tank	17.17 gal.(65 L)
	Hydraulic tank	12.2 gal.(46 L)
	Maximum digging height	18'6" (5,650 mm)
	Maximum digging depth	11'11" (3,640 mm)
	Maximum dumping height	13'2" (4,010 mm)
Working Range	Maximum vertical wall digging depth	8'10" (2,690 mm)
	Minimum swing radius	7'12" (2,430 mm)
	Maximum digging reach at ground level	19'7" (5,960 mm)
	Maximum digging reach	20'1" (6,110 mm)
Dimensions	Overall length	17'6" (5,340 mm)
	Tail slew radius	3'5" (1,040 mm)
	Tumbler length	6'6" (1,990 mm)
	Track length	14'9" (2,490 mm)
	Dozer blade, maximum reach at ground level	6'7" (1,995 mm)
	Undercarriage length	10'5" (3,185 mm)
	Dozer blade height	16"(400 mm)
	Overall width	6'4" (1,960 mm)
	Track gauge	5'1" (1,560 mm)
	Minimum ground clearance	12" (315 mm)
	Track height	22" (550 mm)
	Ground clearance of counterweight	25" (637 mm)
	Overall height of engine hood	5'7" (1,695 mm)
	Overall height	8'5" (2555 mm)
	Track shoe width	16" (400 mm)
	Working width at maximum right-hand rotation	6'12" (2,130 mm)
	Working width at maximum left-hand rotation	6'5" (1,960 mm)
	Maximum boom offset to the right	32" (815 mm)
	Maximum boom offset to the left	24" (605 mm)
	Maximum boom swing angle to the right	53°
	Maximum boom swing angle to the left	70°

