

Standard Bucket Capacity:
0.33 m³ (0.43 yd³)

SOLID TO SUCCEED.



Operating Weight:
9,250 kg (20,392 lb)

Rated Power:
54.6 kW (73.2 hp)

XE



SMALL EXCAVATORS

XE80U

- ▶ The XE80U comes with every feature you expect from a small excavator in its tonnage.
- ▶ Variable angle boom, 62° to the left and 50° to the right, reduced swing tail, and standard rubber track and angle blade gives you an edge when undertaking operations in confined sites such as utility, garden, and community landscapes.
- ▶ Powered by a reliable 73.2 hp Kubota engine, you can count on it to finish tough jobs in various operating conditions. When it comes to efficiency, versatility is a critical factor. That's why the machine is compatible to multiple attachments that can be installed within a short period of time with its hydraulic quick coupler. You will finish the operations with ease and comfort in the jobsite.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

TECHNICAL SPECIFICATIONS

ITEM	CONTENT	XE80U
Engine	Make/model	Kubota/V33073CRTE5
	No. of cylinders	4
	Rated power at 2200 rpm	54.6 kW/2200 rpm (73.2 hp)
	Piston displacement	3.3 L (0.87 gal)
	Idle (low - high)	1200-2000 rpm
	Max. torque at 1500 rpm	265 N · m/1500 rpm (195 lbf · ft)
Speed & Traction	Travel speed (low - high)	2.7 - 4.9 km/h (1.68 - 3.04 mph)
	Maximum traction force	64kN (14388 lbf)
	Gradeability	70%/35°
Digging Forces (ISO 6015)	Digging force, standard arm (ISO 6015)	41 kN (9217 lbf)
	Digging force, bucket (ISO 6015)	64 kN (14388 lbf)
Fluid Capacity	Fuel tank	130 L (34.3 gal)
	Hydraulic oil tank	110 L (29.1 gal)
	Engine oil	10 L (2.6 gal)
Working Range	Maximum digging height	6850 mm (22'6")
	Maximum digging depth	3993 mm (13'1")
	Maximum dumping height	4988 mm (16'4")
	Maximum vertical wall digging depth	1935 mm (6'4")
	Maximum digging reach	7145 mm (23'5")
	Minimum swing radius	3205 mm (10'6")
Dimensions	Overall length	6585 mm (21'7")
	Overall width	2300 mm (7'7")
	Overall height	2730 mm (8'11")
	Width of platform	2250 mm (7'5")
	Length of crawler	2900 mm (9'6")
	Overall width of chassis	2300 mm (7'7")
	Width of crawler	450 mm (18")
	Track length on ground	2272 mm (7'5")
	Crawler gauge	1850 mm (6'1")
	Clearance under counterweight	818.5 mm (32")
	Minimum ground clearance	386.5 mm (15")
	Minimum tail swing radius	1450/1545 mm (4'9"/5'1")
	Height of track	692 mm (27")

HYDRAULIC SYSTEM

	TYPE	DISPLACEMENT	MAX.FLOW	RELIEF VALVE PRESSURE
Main (load sensing)	Load sensing pump	104.3 cm ³ /rev (6.36 in ³ /rev)	219 L/min (57.9 gal)	30 Mpa (4351 psi)

