

SOLID TO SUCCEED.



XC7 SV12



XC7-SV12

► **Highlight:**

The machine is designed with ROPS/FOPS certified cab. Suspension seat provides greater comfort for the operator. The quick coupler and third function are standard, can be easily and quickly switching between a range of attachments.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



PARAMETER LIST

A	Overall length	7,340 mm	24.08 ft
B	Overall width	2,350 mm	7.71 ft
C	Overall height	3,437 mm	11.27 ft
D	Cab height	2,868 mm	9.40 ft
E	Wheelbase	2,180 mm	7.15 ft
G	Front wheel width	2,207 mm	7.24 ft
H	Rear wheel width	2,279 mm	7.47 ft
I	Total weight	7,600 mm	16,755.13 lb
J	Max. traction force	76 kN	76 kN
K	Bucket retraction angle	74 mm	0.24 ft
L	Bucket retraction angle	42°	42°
M	Maximum dumping height	2,776 mm	9.10 ft
N	Dumping range under maximum dumping height	832 mm	2.72 ft
O	Dumping Angle	45°	45°
P	Maximum working height	4,366 mm	14.32 ft
Q	Maximum height of bucket pin	3,495 mm	11.46 ft
R	Rated load	2,500 kg	5,511.5 lb
S	Maximum breakout force (Bucket cylinder)	66 kN	66 kN
T	Bucket capacity	1 m ³	1.31 yd ³
U	Maximum lifting height and lifting capacity	31 kN	31 kN
V	Total cycling time	8S	8S
W	Total cycling time	8S	8S
X	Total cycling time	8S	8S

