

SOLID TO SUCCEED.



XC7



XC7-TV12

► **Highlight:**

The Yanmar engine provide a output 53.7kW/72hp With unmatched performance. the hydrostatic Transmission provides quick travel Response and aggressive drive. Two speed is standard with hydraulic released parking brakes. The suspension seat provides further comfortable and less fatigue environment.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

PARAMETER LIST

A	Maximum overall height	4,153 mm	13.62 ft
B	Height to hinge pin at maximum lift	3,300 mm	10.82 ft
C	Height to top of cab	2,100 mm	6.89 ft
D	Clearance bucket bottom to ground	3,136 mm	10.29 ft
E	Length without bucket	2,915 mm	9.56 ft
F	Length with bucket	3,786 mm	12.42 ft
G	Dump angle (full lift height)	40°	
H	Dump height at maximum lift and dump	2,615 mm	8.58 ft
K	Bucket rollback at ground level	26°	
L	Bucket rollback at maximum lift	84°	
J	Reach at maximum lift and dump	1,025 mm	3.36 ft
M	Wheelbase	1,640 mm	5.38 ft
O	Angle of departure	31°	
P	Ground clearance	216 mm	0.71 ft
R	Front turning radius without bucket	1,466 mm	4.81 ft
S	Front turning radius with bucket	2,274 mm	7.46 ft
T	Rear turning radius	1,809 mm	5.93 ft
U	Bumper overhang behind Rear Axle	885 mm	2.9 ft
V	Tread	1,595 mm	5.23 ft
W	Width without bucket	2,045 mm	6.71 ft
X	Width bucket	2,000 mm	6.56 ft

