

SOLID TO SUCCEED.  **XCMG**



COMPACT MINI LOADER

XC968U

▶ **Highlight:**

The color monitor displays working hours, temperature, fuel level, maintenance alerts, and more. The electrically actuated, wide-angle tilting hood ensures easy access for daily maintenance, including engine air filters and oil checks.

Our quick coupler meets JRB standards, widely used in North America. This universal design allows one machine to operate multiple attachments—and one attachment to fit machines of different sizes.

XCMG North America Corporation
305 Equipment Ct. Suite A
Lawrenceville, GA 30043
+1 725-605-2777
letsgo@xcmgusa.com
xcmg-usa.com



SCAN ME

DIMENSIONS & SPECIFICATIONS		GENERAL PURPOSE QUICK CHANGE				HIGH LIFT QUICK CHANGE			
		3.5m ³	4.6 yd ³	5.0m ³	6.5 yd ³	3.5m ³	4.6 yd ³	5.0m ³	6.5 yd ³
	Bucket capacity	3.5m ³	4.6 yd ³	5.0m ³	6.5 yd ³	3.5m ³	4.6 yd ³	5.0m ³	6.5 yd ³
A	Height to Top of Exhaust Pipe	3160 mm	10.37 ft ³	3160 mm	10.37 ft	3160 mm	10.37 ft	3160 mm	10.37 ft
B	Height to Top of Cabin	3505 mm	11.50 ft ³	3505 mm	11.50 ft	3505 mm	11.50 ft	3505 mm	11.50 ft
C	Height to Top of Warning Beacon	3860 mm	12.66 ft	3860 mm	12.66 ft	3860 mm	12.66 ft	3860 mm	12.66 ft
D	Ground clearance	425 mm	1.39 ft	425 mm	1.39 ft	425mm	1.39 ft	425mm	1.39 ft
E	Wheelbase	3450 mm	11.32 ft	3450 mm	11.32 ft	3450 mm	11.32 ft	3450 mm	11.32 ft
F	Overall Length (without bucket)	7100 mm	23.29 ft	7100 mm	23.29 ft	7475 mm	24.52 ft	7475 mm	24.52 ft
G	Shipping length (with bucket level on ground)	8650 mm	28.38 ft	8895 mm	29.18 ft	8900 mm	29.20 ft	8900 mm	29.20 ft
H	Hinge Pin Height at Carry Position	470 mm	1.54ft	470 mm	1.54 ft	550mm	1.80 ft	550mm	1.80 ft
I	Hinge Pin Height at Maximum Lift	4270 mm	14.01 ft	4270 mm	14.01 ft	4600 mm	15.09 ft	4600 mm	15.09 ft
J	Lift Arm Clearance at Maximum lift	3705 mm	12.16 ft	3705 mm	12.16 ft	3866 mm	12.68 ft	3866 mm	12.68 ft
K	Dump Clearance at Maximum lift and 45° Discharge	3030 mm	9.94 ft	2860 mm	9.38 ft	3390 mm	11.12 ft	3225 mm	10.58 ft
L	Reach at Maximum Lift and 45° Discharge	1345 mm	4.41 ft	1515 mm	4.97 ft	1325 mm	4.35 ft	1505 mm	4.94 ft
M	Dump Angle at Maximum Lift and Dump (on stops)	45°	45°	45°	45°	43°	43°	43°	43°
N	Roll back Angle	Ground	42°	42°	42°	43°	43°	43°	43°
		Carry	46°	46°	46°	49°	49°	49°	49°
O	Turning Radius Outside of Tires	6025 mm	19.77 ft	6025 mm	19.77 ft	6025 mm	19.77 ft	6025 mm	19.77 ft
P	Turning Radius Inside of Tires	3460 mm	11.35 ft	3460 mm	11.35 ft	3460 mm	11.35 ft	3460 mm	11.35 ft
Q	Width over Tires (unloaded)	2865 mm	9.40 ft	2865 mm	9.40 ft	2865 mm	9.40 ft	2865 mm	9.40 ft
R	Tread Width	2265 mm	7.43 ft	2265 mm	7.43 ft	2265 mm	7.43 ft	2265 mm	7.43 ft
S	Dig Depth	120 mm	0.39 ft	120 mm	0.39 ft	120 mm	0.39 ft	120 mm	0.39 ft
T	Overall Height	5825 mm	19.11 ft	5950 mm	19.52 ft	6160 mm	20.21 ft	6285 mm	20.62 ft
U	Turning Radius Over bucket	6945 mm	22.79 ft	7150 mm	23.46 ft	7060 mm	23.16 ft	7265 mm	23.84 ft
V	Gradeability	29°	29°	29°	29°	29°	29°	29°	29°
W	Bucket Width	2996 mm	9.83 ft	3200 mm	10.50 ft	2996 mm	9.83 ft	3200 mm	10.50 ft
X	Articulation Angle	40°	40°	40°	40°	40°	40°	40°	40°
Tipping load	Static tipping load: straight	14500 kg	31967 lb	14100 kg	31085 lb	13100 kg	28881 lb	12500 kg	27558 lb
	40° full turn	13400 kg	29542 lb	13020 kg	28704 lb	12500 kg	27558 lb	11500 kg	25353 lb
Breakout force		205 kN	46086 lbf	175 kN	39342 lbf	190 kN	42714 lbf	165 kN	307094 lbf
Operating weight		21600 kg	47620 lb	21980 kg	48458 lb	21650 kg	47730 lb	22030 kg	48568 lb

