



SOLID TO SUCCEED.

Standard Bucket Capacity:  
0.32 - 0.6 m<sup>3</sup> (0.42 - 0.78 yd<sup>3</sup>)

Rated Power:  
90 kW (121 hp)

Operating Weight:  
15,000 kg (33,069 lb)



HYDRAULIC EXCAVATORS

# XE135U

- ▶ The newly engineered XE135U builds on the concept of robust power and longer durability of mid size excavators of XCMG. All systems have been designed on the basis of harmonious matching of sufficient power, hydraulic flow, versatility, low fuel consumption and equipped with exhaust treatment system to meet the EPA regulations.
- ▶ If you are looking for a tough machine from a durable brand you can trust to get your work done with efficiency look no further than our XE135U. Its versatile design and innovative features deliver the performance you expect to do various difficult jobs.

XCMG North America Corporation  
305 Equipment Ct. Suite A  
Lawrenceville, GA 30043  
+1 725-605-2777  
letsgo@xcmgusa.com  
xcmg-usa.com



SCAN ME

# TECHNICAL SPECIFICATIONS

ITEM	CONTENT	XE135U
Engine	Model	Cummins F3.8
	No. of cylinders	4
	Rated power at 2100 rpm (SAE J1995)	90 kW (121 hp) at 2200 rpm
	Max. torque at 1500 rpm	500 N · m (369 lb.ft)
	Idle (low-high)	950 - 1100 rpm
	Piston displacement	3.8 L (232 in <sup>3</sup> )
Pump flow & System pressure	Main pumps, type:	2 x variable displacement tandem axial piston pumps
	Maximum flow at 1800 rpm	2x120+53 L/min (2x31.7+11.7 gal/min)
	Pilot pumps, type:	Gear pump
	Maximum flow at 1800 rpm	18 L/min (4.8 gal/min)
Speed & Traction	Travel speed (low - high)	2.9 - 4.7 km/h (1.8 - 2.9 mph)
	Maximum traction force	121 kN (27202 lbf)
	Maximum gradeability	70% / 35°
Digging Forces	Bucket (Normal/Press. Up) - kN/lbf	250 L (66 gal)
	Arm (Normal/Press. Up) - kN/lbf	25 L (6.6 gal)
Fluid Capacity	Fuel tank	95 L (25.1 gal)
	Urea (def) tank	11 L (2.9 gal)
	Hydraulic oil tank	107/24055
	Engine oil	80/17985
Working Range	Maximum digging reach	8295/27'3"
	Maximum digging depth	5535/18'2"
	Maximum loading height	6160/20'3"
	Minimum loading height	2095/6'10"
	Maximum digging height	8630/28'4"
	Maximum vertical wall depth	4580/15"
Dimensions	Minimum swing radius	2475/8'1"
	Tail swing radius	2370/7'9"
	Shipping height (boom)	2930/9'7"
	Shipping height (Cab)	3035/9'11"
	Shipping length	7780/25'6"
	Shipping width	2590/8'6"
	Counterweight clearance	931/37"
	Height over cab	2870/9'5"
	House width	2490/8'2"
	Cab height above house	766/30"
	Cab width	1096/3'7"
	Tumbler distance	2910/9'7"
	Track length	3630/11'11"
	Undercarriage width	2590/8'6"
	Shoe width std.	600/24"
	Track height	803/32"
Ground clearance	476/19"	

