

SOLID TO SUCCEED.



Standard Bucket Capacity:  
1.2 m<sup>3</sup> (1.57 yd<sup>3</sup>)

Operating Weight:  
23,500 kg (51,809 lb)

Rated Power:  
129 kW (173 hp)



HYDRAULIC EXCAVATORS

# XE225U

- ▶ The newly engineered XE225U builds on its reputation as one of the most sold and appreciated excavators of XCMG. All features have been designed based on evaluation of customer demands including sufficient power and hydraulic flow, versatility, low fuel consumption and emissions.
- ▶ If you are looking for a tough machine from a durable brand you can trust to get your work done with efficiency, look no further than our XE225U. Its versatile design and innovative features delivery the performance you expect to do various difficult jobs.

XCMG North America Corporation  
305 Equipment Ct. Suite A  
Lawrenceville, GA 30043  
+1 725-605-2777  
letsgo@xcmgusa.com  
xcmg-usa.com



SCAN ME

# TECHNICAL SPECIFICATIONS

ITEM	CONTENT	XE225U
Engine	Model	Cummins B6.7
	No. of cylinders	6
	Rated power at 2100 rpm (SAE J1995)	129 kW (173 hp)
	Max. torque at 1300 rpm	881 N • m (650 ft • lb)
	Piston displacement	6.7 L (1.8 gal)
	Main pumps, type:	2 x Variable pump
Pump flow & System pressure	Maximum flow	2x220 L/min (2x58.1 gal/min)
	Pilot pumps, type:	Gear pump
	Maximum flow	17 L/min (4.5 gal/min)
	Travel speed (low - high)	3.1 - 5.8 km/h (1.9/3.6 mph)
Speed & Traction	Maximum traction	214 kN (48109 lbf)
	Maximum gradeability	70% / 35°
	Bucket (Normal/Press. Up) - kN/lbf	149/33497
Digging Forces (ISO)	Arm (Normal/Press. Up) - kN/lbf	111/24954
	Fuel tank	400 L (105.7 gal)
Fluid Capacity	Urea (def) tank	48 L (10.6 gal)
	Hydraulic oil tank	150 L (39.6 gal)
	Engine oil	24 L (6.3 gal)
	Maximum digging reach	9940/32'7"
Working Range	Maximum digging reach (ground)	9780/32'1"
	Maximum digging depth	6680/21'11"
	Maximum loading height	6780/22'3"
	Minimum loading height	2400/7'10"
	Maximum digging height	9620/31'7"
	Maximum bucket pin height	8240/27'
	Maximum vertical wall depth	5715/18'9"
Dimensions	Maximum digging depth (8' level)	6500/21'4"
	Minimum swing radius	3540/11'7"
	Tail swing radius	3015/9'11"
	Shipping height (boom)	3000/9'10"
	Shipping height (guardrail)	3150/10'3"
	Shipping length	9810/32'2"
	Shipping width	3190/10'6"
	Counterweight clearance	1067/3'6"
	Height over cab	2985/9'8"
	Upper structure width	2830/9'3"
	Cab height above house	1778/5'8"
	Cab width	1095/3'7"
	Tumbler distance	3650/11'11"
	Track length	4445/14'7"
	Track gauge	2390/7'8"
	Shoe width std.	800/31"
	Track height	925/36"
	Ground clearance	485/19"

